



RETREAD AND REPAIR LIQUIDS

The PURPOSE of cements in the retread and repair plant is two fold:

1. To provide Building Tack or an Adhesive Bond to hold the tread or repair material onto the tire prior to curing. This bond is often called "UNCURED" OR "GREEN" Adhesion.
2. To promote Improved Cured Adhesion.

Western Weld Cements were designed to accomplish this purpose. The cements all contain Natural Rubber and Special Tackifiers and Resins to improve both the Green and Cured Adhesion. **Western Weld** Cements are easy to use, fast drying, and have good shelf life.

Western Weld Cements give the user high quality, dependability, and high performance at no extra cost. Uncompromising quality control assures the user consistent uniformity. **Western Weld** Technical Experience and Service is always available.

Western Weld cements are available in QUARTS GALLONS, 5 GALLONS & 55 GALLON DRUMS

BLACK VULCANIZING CEMENT BRUSH TYPE

An excellent Repair cement. Contains special additives to bond to exposed cords such as Nylon, Rayon, Fiberglass, Polyester, and Polyaramid. Use within 15 minutes on exposed Steel for best adhesion. Superior tack and excellent CURED adhesion.

BLACK VULCANIZING CEMENT SPRAY TYPE

An all-purpose cement for both hot capping and pre cure retreading. Also used for repairing. A high tack cement. Excellent CURED adhesion and provides superior bond and tack. Use in Die-size application. **REPLACES EX-451 EXTRUDER HOT TACK STRIP CEMENT.**

RIM SEAL BEAD SEALER BS 140 NON-FLAMMABLE AND FLAMMABLE

A thick, viscous sealant. Bead Sealer seals small troublesome leaks around tire bead of tubeless tires and wheel.

RUBBER SOLVENT

Pure Aliphatic Hydrocarbon, free from oils and impurities. Use for diluting or thinning heavy viscosity cements and tire paint. Use to clean buffed retread and repair surfaces. Use to freshen cushion gum and other uncured rubber stocks.

CHEMICAL VULCANIZING CEMENT

A natural rubber solution containing activators and accelerators which act upon chemical curing tire repair units and materials to effect the chemical cure at room temperature. Available both - Non-Flammable and Flammable.

LIQUID RUBBER BUFFER

A mixture of chemicals which chemically clean the inside of tires prior to mechanical buffing. Removes various mold lubricants and contaminates to maximize adhesion. Available both - Non-Flammable and Flammable.

Elgi Rubber Co., hereby disclaims all warranties, expressed and implied, including, with out limitation, all implied warranties of merchantability and fitness for particular purpose with regard to the goods that are in subject thereof. The liability, if any, of Elgi Rubber Co. shall be limited to the purchase price of the goods, and Elgi Rubber Co. shall in no event be liable for consequential damages. Purchaser must bring any action against Elgi Rubber Co. within one (1) year from the date of sale.

